

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**LuxatempStar**

Revision date: 13.04.2016

Product code: 1300

Page 1 of 5

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

LuxatempStar

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.3. Details of the supplier of the safety data sheet**

Company name:	DMG Chemisch-Pharmazeutische Fabrik GmbH	
Street:	Elbgaustraße 248	
Place:	D-22547 Hamburg	
Telephone:	+49. (0) 40. 84006-0	Telefax: +49. (0) 40. 84006-222
e-mail:	info@dmg-dental.com	
Internet:	www.dmg-dental.com	

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

May cause respiratory irritation.

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Signal word:** Warning**Pictograms:****Hazard statements**

H335	May cause respiratory irritation.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

**Precautionary statements**

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352	IF ON SKIN: Wash with plenty of water.

**2.3. Other hazards**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**LuxatempStar**

Revision date: 13.04.2016

Product code: 1300

Page 2 of 5

**Chemical characterization**

chemical characterization (preparation): Acrylate.-resin.

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
41637-38-1	Dimethacrylate Resin			35-45 %

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****After inhalation**

Exposition vermeiden. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

**After contact with skin**

After contact with skin, wash immediately with: Water and soap.

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

**After ingestion**

Consult physician.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO<sub>2</sub>).**Unsuitable extinguishing media**

High power water jet.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation.

**6.2. Environmental precautions**

Do not empty into drains or the aquatic environment.

**6.3. Methods and material for containment and cleaning up**

Collect mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**Keep container tightly closed in a cool, well-ventilated place.  
Store only in original container.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**LuxatempStar**

Revision date: 13.04.2016

Product code: 1300

Page 3 of 5

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****8.2. Exposure controls****Protective and hygiene measures**

When using do not eat or drink.

**Eye/face protection**

Tightly sealed safety glasses.

**Hand protection**

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

**Respiratory protection**

The following must be prevented: inhalation.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Paste
Colour:	characteristic
Odour:	ester

	Test method
pH-Value (at 20 °C):	ca. 7
<b>Changes in the physical state</b>	
Initial boiling point and boiling range:	>250 °C
point of decomposition:	200 °C
Flash point:	>150 °C
Ignition temperature:	>380 °C
Vapour pressure: (at 20 °C)	1 hPa
Density:	1,5 g/cm <sup>3</sup>
Water solubility:	10 g/L
Vapour density:	1

**SECTION 10: Stability and reactivity****10.4. Conditions to avoid**

heat. Light.

Decomposition takes place from temperatures above: 200 °C

Decomposition under formation of: Acrylate.

**10.5. Incompatible materials**

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

**10.6. Hazardous decomposition products**

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent). nitrogen oxides (NOx).

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**LuxatempStar**

Revision date: 13.04.2016

Product code: 1300

Page 4 of 5

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

LD50: Rat. 5000 mg/kg

**Irritation and corrosivity**

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye:

**Additional information on tests**

Contains Methacrylic esters.: May produce an allergic reaction.

**SECTION 12: Ecological information****12.1. Toxicity**

Acute fish toxicity LC50: &gt;360 mg/l/48h

**12.2. Persistence and degradability**

Preparation not tested.

**Further information**

Do not empty into drains or the aquatic environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Paste: Carry out a burning of hazardous waste according to official regulations.

**Waste disposal number of waste from residues/unused products**

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances  
Classified as hazardous waste.

**SECTION 14: Transport information****Other applicable information**

Not a hazardous material with respect to these transportation regulations.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information****SECTION 16: Other information****Relevant H and EUH statements (number and full text)**

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### LuxatempStar

Revision date: 13.04.2016

Product code: 1300

Page 5 of 5

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*